ELSEVIER

INDEX

Author/Title Index

Anthony, G. T., Anthony, H. M., Bittner, B., Butler, B. P., Cox, M. G., Driescher, R., Ellingsen, R., Forbes, A. B., Gross, H., Hannaby, S. A., Harris, P. M., and Kok, J. Reference software for finding Chebyshev best-fit geometric elements, 19:28
Anthony, H. M.: See Anthony, G. T.
Arcona, C., and Dow, T. A. A new technique for studying the chip information process in diamond turning, 18:157
Arii, S.: See Mizumoto, H.
Atherton, P. D.: See Xu, Y.

Badami, V. G., Smith, S. T., Raja, J., and Hocken, R. J. A portable three-dimensional stylus profile measuring instument, 18:147
Bittner, B.: See Anthony, G. T.
Bochardt, B.: See Estler, W. T.
Burdekin, M.: See Kwon, H. D.
Butler, B. P.: See Anthony, G. T.

Chen, C.-D.: See Su, D.-C.
Cheraghi, S. H., Lim, H. S., and Motavalli, S. Straightness and flatness tolerance evaluation: an optimization approach, 18:30
Chetwynd, D. G., Liu, X., and Smith, S. T. A controlled-force stylus displacement probe, 19:104
Chetwynd, D. G.: See Pawlus, P.
Chiu, M.-H.: See Su, D.-C.
Cox, M. G.: See Anthony, G. T.
Croarkin, M. C.: See Vorburger, T. V.

Dow, T. A.: See Arcona, C.
Dow, T. A.: See Miller, M. H.
Driescher, R.: See Anthony, G. T.

Eberhardt, K.: See Estler, W. T.
Ellingsen, R.: See Anthony, G. T.
Estler, W. T., Phillips, S. D., Bochardt, B., Hopp, T., Witzgall, C., Levenson, M., Eberhardt, K., McClain, M., Shen, Y., and Zhang, X. Error compensation for CMM touch trigger probes, 19:84
Evans, C. J.: See Paul, E.

Forbes, A. B.: See Anthony, G. T.
Friedrich C. R.: See Vasile, M. J.
Fu, J. C., Troy, C. A., and Mori, K. Chatter classification by entropy functions and morphological processing in cylindrical traverse grinding, 18:110
Fujii, S.: See Shibata, T.

Gao, W., Kiyono, S., and Nomura, T. A new multiprobe method of roundness measurements, 19:37
Ge, Z.: See Kiyono, S.
Giauque, C. H. W.: See Vorburger, T. V.
Goto, K.: See Mizumoto, H.
Gross, H.: See Anthony, G. T.

Haitjema, H. Dynamic probe calibration in the μm region with nanometric accuracy, 19:97
Hannaby, S. A.: See Anthony, G. T.
Harb, S.: See Miller, J.A.
Harris, P. M.: See Anthony, G. T.
Hocken, R. J.: See Badami, V. G.
Hocken, R.: See Miller, J. A.
Holmes, M., and Trumper, D. Magnetic/fluid-bearing stage for atomic-scale motion control (the angstrom stage), 18:38
Hopp, T.: See Estler, W. T.

Ikeda, M.: See Shibata, T.

Jouaneh, M.: See Yang, R.

Kami, Y..: See Mizumoto, H.
Kawamoto, M.: See Mizumoto, H.
Kikkeri, B.: See Vasile, M. J.
King, T.: See Xu, W.
Kiyono, S., and Ge, Z. Subnanometric calibration of a differential interferometer, 19:186
Kiyono, S.: See Gao, W.
Kohno, T.: See Uda, Y.
Kok, J.: See Anthony, G. T.
Krystek, M. A fast Gauss filtering algorithm for roughness measurements, 19:197
Kwon, H. D., and Burdekin, M. Development and application of a system for evaluating the feed-drive errors on computer numerically controlled machine tools, 19:132

Lévesque, B. A continuous tolerance system, 19:19
Levenson, M.: See Estler, W. T.
Lim, H. S.: See Cheraghi, S. H.
Liu, X.: See Chetwynd, D. G.

Makino, E.: See Shibata, T.
Malburg, M. C.: See Nielsen, H. S.
Mangamelli, A.: See Paul, E.
Marsh, E. R., and Slocum, A. H. An integrated approach to structural damping, 18:103
McClain, M.: See Estler, W. T.
McElhannon, R.: See Vasile, M. J.
McGlauflin, M. L.: See Paul, E.
Miller, J. A., Hocken R., Smith, S. T., and Harb, S. X-Ray calibrated tunneling system utilizing a dimensionally stable nanometer positioner, 18:95
Miller, M. H., and Dow, T. A. Wheel speed equilibria in precision contour grinding, 19:147
Mize, C. D.: See Srinvasa, N.
Mizumoto, H., Arii, S., Kami, Y., Goto, K., Yamamoto, T., and Kawamoto, M. Active inherent restrictor for air-bearing spindles, 19:140
Mori, K.: See Fu, J. C.
Motavalli, S.: See Cheraghi, S. H.

Nielsen, H. S., and Malburg, M. C. Traceability and correlation in roundness measurement, 19:174
Nomura, T.: See Gao, W.

Paul, E., Evans, C. J., Mangamelli, A., McGlauflin, M. L., and Polvani, R. S. Chemical aspects of tool wear in single point diamond turning, 18:4
Pawlus, P., and Chetwynd, D. G. Efficient characterization of surface toopography in cylinder bores, 19:163
Phillips, S. D.: See Estler, W. T.
Polvani, R. S.: See Paul, E.

Raja, J.: See Badami, V. G.
Renegar, T. B.: See Vorburger, T. V.

Schmiechen, P., and Slocum, A. Analysis of kinematic systems: a generalized approach, 19:11
Schweizer, R.: See Yang, R.

Precision Engineering 19:202–204, 1996

© Elsevier Science Inc., 1996

655 Avenue of the Americas, New York, NY 10010

0141-6359/96/$15.00
PII S0141-6359(96)00054-2

ELSEVIER

INDEX

Author/Title Index

Anthony, G. T., Anthony, H. M., Bittner, B., Butler, B. P., Cox, M. G., Driescher, R., Ellingsen, R., Forbes, A. B., Gross, H., Hannaby, S. A., Harris, P. M., and Kok, J. Reference software for finding Chebyshev best-fit geometric elements, 19:28
Anthony, H. M.: See Anthony, G. T.
Arcona, C., and Dow, T. A. A new technique for studying the chip information process in diamond turning, 18:157
Arii, S.: See Mizumoto, H.
Atherton, P. D.: See Xu, Y.

Badami, V. G., Smith, S. T., Raja, J., and Hocken, R. J. A portable three-dimensional stylus profile measuring instument, 18:147
Bittner, B.: See Anthony, G. T.
Bochardt, B.: See Estler, W. T.
Burdekin, M.: See Kwon, H. D.
Butler, B. P.: See Anthony, G. T.

Chen, C.-D.: See Su, D.-C.
Cheraghi, S. H., Lim, H. S., and Motavalli, S. Straightness and flatness tolerance evaluation: an optimization approach, 18:30
Chetwynd, D. G., Liu, X., and Smith, S. T. A controlled-force stylus displacement probe, 19:104
Chetwynd, D. G.: See Pawlus, P.
Chiu, M.-H.: See Su, D.-C.
Cox, M. G.: See Anthony, G. T.
Croarkin, M. C.: See Vorburger, T. V.

Dow, T. A.: See Arcona, C.
Dow, T. A.: See Miller, M. H.
Driescher, R.: See Anthony, G. T.

Eberhardt, K.: See Estler, W. T.
Ellingsen, R.: See Anthony, G. T.
Estler, W. T., Phillips, S. D., Bochardt, B., Hopp, T., Witzgall, C., Levenson, M., Eberhardt, K., McClain, M., Shen, Y., and Zhang, X. Error compensation for CMM touch trigger probes, 19:84
Evans, C. J.: See Paul, E.

Forbes, A. B.: See Anthony, G. T.
Friedrich C. R.: See Vasile, M. J.
Fu, J. C., Troy, C. A., and Mori, K. Chatter classification by entropy functions and morphological processing in cylindrical traverse grinding, 18:110
Fujii, S.: See Shibata, T.

Gao, W., Kiyono, S., and Nomura, T. A new multiprobe method of roundness measurements, 19:37
Ge, Z.: See Kiyono, S.
Giauque, C. H. W.: See Vorburger, T. V.
Goto, K.: See Mizumoto, H.
Gross, H.: See Anthony, G. T.

Haitjema, H. Dynamic probe calibration in the μm region with nanometric accuracy, 19:97
Hannaby, S. A.: See Anthony, G. T.
Harb, S.: See Miller, J.A.
Harris, P. M.: See Anthony, G. T.
Hocken, R. J.: See Badami, V. G.
Hocken, R.: See Miller, J. A.
Holmes, M., and Trumper, D. Magnetic/fluid-bearing stage for atomic-scale motion control (the angstrom stage), 18:38
Hopp, T.: See Estler, W. T.

Ikeda, M.: See Shibata, T.

Jouaneh, M.: See Yang, R.

Kami, Y..: See Mizumoto, H.
Kawamoto, M.: See Mizumoto, H.
Kikkeri, B.: See Vasile, M. J.
King, T.: See Xu, W.
Kiyono, S., and Ge, Z. Subnanometric calibration of a differential interferometer, 19:186
Kiyono, S.: See Gao, W.
Kohno, T.: See Uda, Y.
Kok, J.: See Anthony, G. T.
Krystek, M. A fast Gauss filtering algorithm for roughness measurements, 19:197
Kwon, H. D., and Burdekin, M. Development and application of a system for evaluating the feed-drive errors on computer numerically controlled machine tools, 19:132

Lévesque, B. A continuous tolerance system, 19:19
Levenson, M.: See Estler, W. T.
Lim, H. S.: See Cheraghi, S. H.
Liu, X.: See Chetwynd, D. G.

Makino, E.: See Shibata, T.
Malburg, M. C.: See Nielsen, H. S.
Mangamelli, A.: See Paul, E.
Marsh, E. R., and Slocum, A. H. An integrated approach to structural damping, 18:103
McClain, M.: See Estler, W. T.
McElhannon, R.: See Vasile, M. J.
McGlauflin, M. L.: See Paul, E.
Miller, J. A., Hocken R., Smith, S. T., and Harb, S. X-Ray calibrated tunneling system utilizing a dimensionally stable nanometer positioner, 18:95
Miller, M. H., and Dow, T. A. Wheel speed equilibria in precision contour grinding, 19:147
Mize, C. D.: See Srinvasa, N.
Mizumoto, H., Arii, S., Kami, Y., Goto, K., Yamamoto, T., and Kawamoto, M. Active inherent restrictor for air-bearing spindles, 19:140
Mori, K.: See Fu, J. C.
Motavalli, S.: See Cheraghi, S. H.

Nielsen, H. S., and Malburg, M. C. Traceability and correlation in roundness measurement, 19:174
Nomura, T.: See Gao, W.

Paul, E., Evans, C. J., Mangamelli, A., McGlauflin, M. L., and Polvani, R. S. Chemical aspects of tool wear in single point diamond turning, 18:4
Pawlus, P., and Chetwynd, D. G. Efficient characterization of surface toopography in cylinder bores, 19:163
Phillips, S. D.: See Estler, W. T.
Polvani, R. S.: See Paul, E.

Raja, J.: See Badami, V. G.
Renegar, T. B.: See Vorburger, T. V.

Schmiechen, P., and Slocum, A. Analysis of kinematic systems: a generalized approach, 19:11
Schweizer, R.: See Yang, R.

Precision Engineering 19:202–204, 1996

© Elsevier Science Inc., 1996

655 Avenue of the Americas, New York, NY 10010

0141-6359/96/$15.00
PII S0141-6359(96)00054-2

Seering, W. P.: See Singhose, W. E.
Shen, Y.: See Estler, W. T.
Shibata, T., Fujii, S., Makino, E., and Ikeda, M. Ductile-regime turning mechanism of single-crystal silicon, 18:129
Singer, N. C.: See Singhose, W. E.
Singhose, W. E., Seering, W. P., and Singer, N. C. Improving repeatability of coordinate measuring machines with shaped command signals, 18:138
Slocum, A. H.: See Marsh, E. R.
Slocum, A.: See Schmiechen, P.
Smith, S. T.: See Badami, V. G.
Smith, S. T.: See Chetwynd, D. G.
Smith, S. T.: See Miller, J. A.
Smith, S. T.: See Xu, Y.
Song, J. F.: See Vorbruger, T. V.
Srinivasa, N., and Ziegert, J. C. Automated measurement and compensation of thermally induced error maps in machine tools, 19:111
Srinivasa, N., Ziegert, J. C., and Mize, C. D. Spindle thermal drift measurement using the laser ball bar, 18:118
Su, D.-C., Chiu, M.-H., and Chen, C.-D. Simple two-frequency laser, 18:161

Taylor, J. B., and Tu, J. F. Precision *X–Y* microstage with maneuverable kinematic coupling mechanism, 18:85
Troy, C. A.: See Fu, J. C.
Trumper, D.: See Holmes, M.
Tu, J. F.: See Taylor, J. B.

Uda, Y., Kohno, T., and Yazawa, T. In-process measurement and workpiece-referred form accuracy control system (WORFAC): application to cylindrical turning using an ordinary lathe, 18:50

Vasile, M. J., Friedrich, C. R., Kikkeri, B., and McElhannon, R. Micrometer-scale machining: tool fabrication and initial results, 19:179
Vorburger, T. V., Song, J. F., Giauque, C. H. W., Renegar, T. B., Whitenton, E. P., and Croarkin, M. C. Stylus-laser surface calibration system, 19:156

Whitenton, E. P.: See Vorburger, T. V.
Witzgall, C.: See Estler, W. T.

Xu, W., and King, T. Flexure hinges for piezoactuator displacement amplifiers: flexibility, accuracy, and stress considerations, 19:4
Xu, Y., Smith, S. T., and Atherton, P. D. A metrological scanning force microscope, 19:46

Yamamoto, T.: See Mizumoto, H.
Yang, R., Jouaneh, M., and Schweizer, R. Design and characterization of a low-profile micropositioning stage, 18:20
Yazawa, T.: See Uda, Y.

Zhang, X.: See Estler, W. T.
Ziegert, J. C.: See Srinivasa, N.
Ziegert, J. C.: See Srinivasa, N.

Keyword Index

3-point method, 19:37
Active restrictor, 19:140
Actuator, 19:4
Aerostatic bearing, 19:140
Air bearing spindle, 19:140
Algorithm, 19:197
Angstrom resolution, 18:38
Anisotropic surface topography, 19:163
Automation, 19:19

Best fit, 19:28

C program, 19:197
Calibration, 19:156, 174
Capacitance sensor, 19:46
Capacitive sensing, 19:104
Chebyshev approximation, 19:28
Chip geometry, 18:157
Circle test, 19:132
Combinatorics, 19:28
Comparison calibration, 19:186
Contour grinding, 19:147
Contouring errors, 19:132
Control line rotation method, 18:30
Control systems, 18:50
Coordinate measuring machine, 18:138, 19:28, 84
Crystallographic orientation dependence, 18:129
Cutting forces, 18:157
Cylindrical traverse grinding, 18:110

d electron complexes, 18:4
Diamond turning, 18:4, 129, 157
Diamonds, 18:4
Differential interferometer, 19:186
Dimensional metrology, 19:84
Displacement amplifier, 19:4
Displacement measurement, 19:186
Ductile-regime turning mechanism, 18:129
Ductile-regime turning, 18:129
Dynamic calibration, 19:97

Efficiency, 19:4
Electroless nickel, 18:4
Electron tunneling, 18:95
Electro-optic modulator, 18:161
Elliptical hinge, 19:4
Entropy functions, 18:110
Error compensation cutting tests, 19:111
Error correction, 19:84
Experimental measurements, 18:157

Feed-drive errors, 19:132
Filtering, 19:174, 197
Flatness, 18:30
Flexure hinge, 18:20, 19:4
Force control, 19:104
Force probe, 19:46
Form accuracy, 18:50
Friction, 19:11

Fringe counting, 19:186
Fringe interpolation, 19:186

Geometric elements, 19:28
Geometric form, 19:28
Global solutions, 19:28
Grinding energy, 19:147
Grinding spindles, 19:147

Hertz deflection, 19:11
Hinge-profile, 19:4

Infinite stiffness, 19:140
Inherent restrictor, 19:140
In-process measurement, 18:50
Input shaping, 18:138

Kinematic coupling, 18:85
Kinematic design, 19:11

Laser ball bar, 18:118, 19:111
Laser interferometer, 19:97
Least-square method, 18:30
Linearity error, 19:186

Machine accuracy, 19:132
Machining process monitoring, 18:110
Magnetically suspended, 18:38
Mechanical advantage, 18:85
Metrology, 18:95, 19:37, 19:174
Micromachining, 19:179

Micropositioning stage, 18:20
Microstage, 18:85
Microtools, 19:179
Minimum zone method, 18:30
Mixed method, 19:37
Modeling, 19:84
Monolithic flexures, 18:95
Morphological processing, 18:110
Motor, 19:4
Multiprobe method, 19:37

Nanometer positioning, 18:95
Nanometrology, 19:97
Nanotechnology, 18:95
Neural network, 19:111

On-machine measurement, 19:37
Optical sensor, 19:37
Optimization method, 18:30
Optimization, 19:19

Phase modulation, 19:186
Piezoacutator, 18:20, 19:46
Piezoelectric actuator, 19:140
Piezoelectric, 19:4
Precision motion control, 18:38
Precision x-y scanning stage, 19:46
Precision, 19:11

Reference software, 19:28
Regenerative chatter classification, 18:110
Repeatability, 19:11
Resolution, 19:37
Right circular hinge, 19:4
Rotational accuracy, 19:140
Roughness measurement, 19:197
Roughness, 19:97, 156
Roundness, 19:37, 19:174

Scanning force microscope (SFM), 19:46
Scanning probe microscope (SPM), 19:46
Screw-wedge-lever, 18:95
Self-calibration, 19:186
Sensor calibration, 19:186
Single-crystal silicon, 18:129
Single-point diamond turning, 18:50
Sinusoidal profiles, 19:156
Slip formation, 18:129
Slip system, 18:129
Spindle error, 19:37
Spindle thermal drifts, 18:118, 19:111
Standards, 19:174
Straightness, 18:30
Structural damping, 18:103
Stylus instrument, 19:97, 104, 156
Stylus-laser, 19:156
Substitute elements, 19:28
Surface digitization, 19:163
Surface measurement, 19:46
Surface metrology, 19:163
Surface profiling, 19:104
Surface roughness, 19:147
Surface texture, 19:156

Thermal errors, 18:118
Tip-convolution, 19:174
Tolerancing, 19:19
Tool wear, 18:4
Tools, 18:4
Total positional errors, 19:111
Touch trigger probes, 19:84
Traceability, 19:156
Transmission electon microscopy characterization, 18:129
Tribochemistry, 18:4
Two-frequency interferometry, 18:161
Two-frequency laser, 18:161

Ultraprecision, 19:179
Uncertainty, 19:156, 174

Vibration, 18:138
Vibration damping, 18:103
Viscoelastomer, 18:103

Wheel speed, 19:147

X-ray interferometry, 18:95